

## Required nails and staples ratios

REGULAR SIDING	2" HAND NAILS		3" HAND NAILS	2 1/2" COIL NAILS (NOT STAINED)	
	SIMPLE NAILING	DOUBLE NAILING		SIMPLE NAILING	DOUBLE NAILING
Siding 4"	15 lbs / 1,000 sq. ft.	N/A	N/A	15 coils / 1,000 sq. ft.	N/A
Siding 6"	15 lbs / 1,000 sq. ft.*	30 lbs / 1,000 sq. ft.**	N/A	15 coils / 1,000 sq. ft.*	30 coils / 1,000 sq. ft.**
Siding 8"	N/A	20 lbs / 1,000 sq. ft.	N/A	N/A	20 coils / 1,000 sq. ft.
Board 10"	N/A	15 lbs / 1,000 sq. ft.	N/A	N/A	15 coils / 1,000 sq. ft.
1" Trims	10 lbs / 1,000 lin ft		N/A	10 coils / 1,000 lin ft	
2" Trims and Batten	N/A		10 lbs / 1,000 lin ft	10 coils / 1,000 lin ft	

### MAIBEC EM+<sup>®</sup> SIDING

1 box of 3000 staples per 750 sq. ft.  
 1 lb of 2" nails per 1,000 sq. ft. for starting course, wall top, opening etc.

\* Rabbeted Bevel 1" x 6"

\*\* Modern 1" x 6", Contemporary 1" x 6", V-Joint 1" x 6", Cove 1" x 6" and Channel 1" x 6"

When installing siding in Coastal regions, stainless steel grade 316 ringed nails must be used for installing siding and trims when nails are used. Failure to comply with this requirement will void the warranties.